



PRODUCT TYPE	COFFEE-MAKER
PRODUCT NAME	DOUBLE INOX INDUCTION



PRODUCT DATASHEET

INDEX

- | | |
|---------------------------------|--------|
| 1. TECHNICAL DATA | pag. 3 |
| 2. DESCRIPTION OF THE APPLIANCE | pag. 4 |



PRODUCT DATASHEET

1. TECHNICAL DATA

SIZE	WEIGHT	HEIGHT	LENGTH	DEPTH
2 cups	280 g	17,5cm	14 cm	8 cm

MATERIAL	<p><u>Stainless steel</u> (upper part, boiler, filter and funnel), in according to the technical standard of UNI EN 10088-1 and UNI EN 10088-3 (classification of stainless steel and technical specifications), DM 21-3-1973 (legislation concerning materials and articles in contact with foodstuffs)</p>
	<p><u>Plastic material</u> (grip holder)</p> <p>The plastic materials used by G.A.T are conform to the standards DM 21-3-1973 (legislation concerning materials and articles in contact with foodstuffs)</p>
	<p><u>Silicone material</u> (Gasket)</p> <p>The silicon gasket used by G.A.T are conform to the standards DM 21-3-1973 (legislation concerning materials and articles in contact with foodstuffs)</p>

2. DESCRIPTION OF THE APPLIANCE

The appliance is composed of the following components (Table 1).

Grip holder	Material: <u>plastic</u> . The grip holder does not get in touch with coffee.
Upper part	Stainless steel AISI 304.
Boiler	Material: <u>Stainless steel</u> AISI 304 with AISI 430 bottom that makes the boiler suitable for induction stoves.
Disk filter	Material: Stainless steel.
Gasket	Silicone Gasket
Safety valve	Opening pressure of safety valve: 2÷3,5 Bar (in according to UNI EN 13248:2004 - Cookware - Coffee makers for domestic use with an independent heat source -. Definitions, requirements and test methods) Control parameter of safety valve (in according to UNI EN 2859/1): - Type of sampling: attributes control - Sampling plan: Simple sampling - Sample units: safety valve - AQL Level: 0
Funnel filter	Material: <u>Stainless steel</u> Dimensional control: conformity of the distance bottom/funnel in accordance with norm UNI EN 13248;2004 (§4.2.6) “Cookware. Coffee makers for domestic use with an independent heat source. Definitions, requirements and test methods”. Acceptance criterion: minimum distance allowed 2 mm

Table n°1 – Components of coffee-maker