



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 1/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **ASCOR EXPRESS LC**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Liquid detergent for cleaning coffee machines.**

1.3. Details of the supplier of the safety data sheet

Name **Murotti Angelo srl**
Full address **Via Caduti di Sabbiuno, 69**
District and Country **40053 Loc. Bazzano- VALSAMOGGIA (BO)**
Italia
Tel. 051 832255
Fax 051 832956

e-mail address of the competent person
responsible for the Safety Data Sheet

info@murottiangelodetersivi.it

1.4. Emergency telephone number

For urgent inquiries refer to

Roma	"	
Osp. Pediatrico Bambino Gesù"		
DEA	tel 06 68593726	
Foggia	Az. Osp. Univ. Foggia	tel 800183459
Napoli	Az. Osp. "A. Cardarelli"	tel 081-5453333
Roma	CAV Policlinico "Umberto I"	tel 06-49978000
Roma	CAV Policlinico "A. Gemelli"	tel 06-3054343
Firenze	Az. Osp. "Careggi" U.O. Toss. Medica	tel 055-7947819
Pavia	CAV C.Naz. Inf. Tossicologica	tel 0382-24444
Milano	Osp. Niguarda Ca' Granda	tel 02-66101029
Bergamo	Az. Osp. Papa Giovanni XXII	tel 800883300
Verona	Az. Ospedaliera Integrata Verona	tel 800011858

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 2/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H314 Causes severe skin burns and eye damage.

Precautionary statements:

P260 Do not breathe dust / fume / gas / mist / vapours / spray.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER / doctor / . . .
P264 Wash . . . thoroughly after handling.

Contains: POTASSIUM HYDROXIDE
SODIUM METASILICATE
ALKYLPOLYGLUCOSIDE C8-C10

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
2-(2-BUTOXYETHOXY)ETHANOL		
INDEX -	$5 \leq x < 10$	Eye Irrit. 2 H319
EC 203-961-6		



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 3/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

CAS 112-34-5

REACH Reg. 01-2119475104-44

POTASSIUM HYDROXIDE

INDEX 019-002-00-8

$5 \leq x < 10$

Met. Corr. 1 H290, Acute Tox. 4 H302, Skin Corr. 1A H314, Eye Dam. 1 H318

EC 215-181-3

Skin Corr. 1B H314: $\geq 2\%$, Skin Irrit. 2 H315: $\geq 0,5\%$, Eye Dam. 1 H318: \geq

2%, Eye Irrit. 2 H319: $\geq 0,5\%$

LD50 Oral: 333 mg/kg

CAS 1310-58-3

REACH Reg. 01-2119487136-33

ALKYLPOLYGLUCOSIDE C8-C10

INDEX -

$3 \leq x < 5$

Eye Dam. 1 H318

EC 500-220-1

CAS 68515-73-1

REACH Reg. 01-2119488530-36

SODIUM METASILICATE

INDEX -

$1 \leq x < 3$

Met. Corr. 1 H290, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335

EC 229-912-9

CAS 10213-79-3

REACH Reg. 01-2119449811-37-

xxx

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 4/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

DO NOT transfer into containers other than the original; risk of fatal errors of exchange with drinks.

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

**Murotti Angelo srl**

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 5/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

ALKYLPOLYGLUCOSIDE C8-C10

Store below 40 °C.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

POTASSIUM HYDROXIDE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	1		4		RESP
VLEP	FRA			2		
WEL	GBR			2		
TLV-ACGIH				2 (C)		

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							1 mg/mc	VND

2-(2-BUTOXYETHOXY)ETHANOL**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	67	10	100,5 (C)	15 (C)	Hinweis
MAK	DEU	67	10	100,5	15	Hinweis
VLA	ESP	67,5	10	101,2	15	
VLEP	FRA	68	10	101,2	15	
VLEP	ITA	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 6/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

TLV-ACGIH	66	10	INHAL					
Predicted no-effect concentration - PNEC								
Normal value of STP microorganisms				200	mg/l			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							67,5 mg/mc	67,5 mg/mc

ALKYLPOLYGLUCOSIDE C8-C10

Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,176	mg/l			
Normal value in marine water				0,0176	mg/l			
Normal value for fresh water sediment				1,516	mg/kg			
Normal value for marine water sediment				0,152	mg/kg			
Normal value for water, intermittent release				0,27	mg/l			
Normal value of STP microorganisms				560	mg/l			
Normal value for the food chain (secondary poisoning)				111,11	mg/kg			
Normal value for the terrestrial compartment				0,654	mg/kg			

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				35,7 mg/kg/d				
Inhalation				124 mg/kg			VND	420 mg/mc
Skin				357000 mg/kg/d				595000 mg/kg/d

SODIUM METASILICATE

Predicted no-effect concentration - PNEC								
Normal value of STP microorganisms				1000	mg/l			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation								6.22 mg/m3
Skin								1,49 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 7/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	brown	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	11,92 (sol. 1%)	
Kinematic viscosity	not available	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	



ASCOR EXPRESS LC

Density and/or relative density	1,07
Relative vapour density	not available
Particle characteristics	not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

POTASSIUM HYDROXIDE

May develop: heat.May corrode: metals.

SODIUM METASILICATE

The aqueous solutions act as: strong bases.Corrodes: aluminium,zinc,tin,aluminium alloys,zinc alloys,tin alloys.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

POTASSIUM HYDROXIDE

Stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

POTASSIUM HYDROXIDE

Develops hydrogen on contact with: metals.Develops heat on contact with: strong acids.Reacts violently with: water.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances.May form peroxides with: oxygen.Develops hydrogen on contact with: aluminium.May form explosive mixtures with: air.



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 9/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

SODIUM METASILICATE

Reacts violently with: acids.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

POTASSIUM HYDROXIDE

Avoid exposure to: sources of heat.Keep away from: oxidising agents,acids,flammable substances,halogens,organic substances.Keep away from: lead,aluminium,copper,tin,sulphur,bronze.Absorbs atmospheric CO₂.

Unstable on exposure to air. Freezing.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

10.5. Incompatible materials

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances,strong acids,alkaline metals.

ALKYLPOLYGLUCOSIDE C8-C10

Avoid contact with: strong acids,strong bases,Strong oxidants,reactive chemicals.

10.6. Hazardous decomposition products

POTASSIUM HYDROXIDE

May develop: flammable gases.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

POTASSIUM HYDROXIDE

LD50 (Oral):	333 mg/kg Rat
--------------	---------------

2-(2-BUTOXYETHOXY)ETHANOL

LD50 (Dermal):	2700 mg/kg Rabbit
LD50 (Oral):	3384 mg/kg Rat
LC50 (Inhalation mists/powders):	29 mg/l

ALKYLPOLYGLUCOSIDE C8-C10

LD50 (Dermal):	> 5000 mg/kg (OECD 402)
LD50 (Oral):	> 5000 mg/kg Rat (OECD 401)

SODIUM METASILICATE

LD50 (Dermal):	> 5000 mg/kg
LD50 (Oral):	> 1150 mg/kg Ratto
LC50 (Inhalation mists/powders):	> 2,06 mg/l



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 11/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

SKIN CORROSION / IRRITATION

Corrosive for the skin

Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class



ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

ALKYLPOLYGLUCOSIDE C8-C10

LC50 - for Fish	> 100 mg/l/96h Brachydanio rerio
EC50 - for Crustacea	> 100 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 10 mg/l/72h Desmodesmus subspicatus
Chronic NOEC for Fish	> 1 mg/l Brachydanio rerio
Chronic NOEC for Crustacea	> 1 mg/l Daphnia magna

POTASSIUM HYDROXIDE

LC50 - for Fish	> 80 mg/l/96h
-----------------	---------------

SODIUM METASILICATE

LC50 - for Fish	> 210 mg/l/96h Brachydanio R.
EC50 - for Crustacea	1700 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 207 mg/l/72h

2-(2-BUTOXYETHOXY)ETHANOL

LC50 - for Fish	> 1300 mg/l/96h Lepomis M.
EC50 - for Crustacea	> 100 mg/l/48h

12.2. Persistence and degradability

ALKYLPOLYGLUCOSIDE C8-C10

Rapidly degradable

POTASSIUM HYDROXIDE

Solubility in water	> 10000 mg/l
---------------------	--------------

Degradability: information not available

2-(2-BUTOXYETHOXY)ETHANOL



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 13/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

The product contains substances that comply with the provisions of Reg 648/04/CE.

12.3. Bioaccumulative potential

2-(2-BUTOXYETHOXY)ETHANOL

Partition coefficient: n-octanol/water

1

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

For cartons of 20 1-litre bottles, ADR 3.4 applies.

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1719

14.2. UN proper shipping name

ADR / RID: CAUSTIC ALKALI LIQUID, N.O.S. MIXTURE

IMDG: CAUSTIC ALKALI LIQUID, N.O.S. MIXTURE



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 14/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

IATA: CAUSTIC ALKALI LIQUID, N.O.S. MIXTURE

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8



IMDG: Class: 8 Label: 8



IATA: Class: 8 Label: 8



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: -

Limited
Quantities: 1
lt

Tunnel
restriction
code: E

Special provision: 274

IMDG: EMS: F-A, S-B

Limited
Quantities: 1
lt

IATA: Cargo:

Maximum
quantity: -
Maximum
quantity: -

Packaging
instructions: -
Packaging
instructions: -

Pass.:

Special provision:

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

Composition (648/04/EC): inf. 5%: nonionic surfactants, EDTA.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

Printed on 19/12/2022

Page n. 15/17

Replaced revision:2 (Printed on: 27/07/2015)

ASCOR EXPRESS LC

Product

Point 3

Contained substance

Point 75

Point 55 2-(2-BUTOXYETHOXY)ETHANOL
REACH Reg.: 01-2119475104-44

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Met. Corr. 1 Substance or mixture corrosive to metals, category 1

Acute Tox. 4 Acute toxicity, category 4

**ASCOR EXPRESS LC**

Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)



Murotti Angelo srl

Revision nr. 3

Dated 06/12/2022

ASCOR EXPRESS LC

Printed on 19/12/2022

Page n. 17/17

Replaced revision:2 (Printed on: 27/07/2015)

- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

11 / 12.